




Robust and vandalism-proof

Technical specifications


- Steel mesh panels with welded steel wires with a mesh of 50 x 200 mm
- Vertical wire (single) = 6 mm
Pallas horizontal wires (double) = 2 x 8 mm
- Pallas Economy (double) = 2 x 6 mm
- Steel box posts (60 x 40 mm)
- Centre-to-centre distance between posts 2,510 mm
- Heras post suitable for the suspension of all types of steel mesh panels
- Height 830 - 2,430 mm
- Post fitted with galvanised base plate (optional)
- The steel mesh panels are connected to the posts using stainless steel straps or are suspended from the post




Panel infill



Pallas connection



Heras suspension post



Staggered

Table of dimensions

Type	Fence height (mm)	Anti-climb over protection
Pallas		
Pallas 80	830	no
Pallas 100	1,030	no
Pallas 120	1,230	no
Pallas 140	1,430	no
Pallas 160	1,630	yes
Pallas 180	1,830	yes
Pallas 200	2,030	yes
Pallas 220	2,230	yes
Pallas 240	2,430	yes
Pallas Economy		
Pallas E 100	1,030	no
Pallas E 120	1,230	no
Pallas E 140	1,430	no
Pallas E 160	1,630	yes
Pallas E 180	1,830	yes
Pallas E 200	2,030	yes
Pallas E 220	2,230	yes
Pallas E 240	2,430	yes

Colour range

The basic finish is: galvanised NEN-EN-ISO 1461.

The following colours are available:

RAL 6005 moss green

RAL 6009 pine green

RAL 6014 Heras green®

RAL 7016 anthracite grey

RAL 7030 stone grey

RAL 9005 deep black

RAL 9010 clear white

Colour combination post /panel infill is possible.

Other colours on request.

Coating

If a coating finish is selected, all galvanised parts are pre-treated after which the powder coating is applied electrostatically. After this the materials are cured in an oven to create the actual coating layer.

Design

Standard

- Universal connection to Heras gates/fence

Options

- Base plate
- Shearing nuts
- Staggered assembly
- Semi-supported end element
- Cast concrete around the intermediate posts